



2025

Fishing Reel & Line

● Reel

● Line

WWW.MWJIGGING.COM

G-MAX Overhead Reel

ALUMINUM
FRAME 6061-T6

Level Drag
System

9+2
STAINLESS STEEL
BEARINGS

OVS
STAINLESS STEEL
GEARS

POWER DRAG
CARBON
WASHER

Super narrow Line cup



Model	Handle Style	Color	Gear Ratio	Weight	Retrieve Per Crank	Max Drag	bearings	Line Capacity
CX1-L	Left	Gray/Gold Red/Gold	6.3:1	450g	99cm	25kg	9+2BB	PE3-400m
CX1-R	Right					25kg		PE5-200m
CX2-L	Left			530g	110cm	35kg		PE4-400m
CX2-R	Right					35kg		PE6-250m

G-MAX Overhead Reel (Version:W)

ALUMINUM
FRAME 6061-T6

Level Drag
System

9+2
STAINLESS STEEL
BEARINGS

OVS
STAINLESS STEEL
GEARS

POWER DRAG
CARBON
WASHER



Model	Handle Style	Color	Gear Ratio	Weight	Retrieve Per Crank	Max Drag	bearings	Line Capacity
CX1W-L	Left	Gray/Gold Red/Gold	6.3:1	480g	99cm	25kg	9+2BB	PE3-480m
CX1W-R	Right					25kg		PE5-240m
CX2W-L	Left			580g	110cm	35kg		PE6-350m
CX2W-R	Right					35kg		PE8-250m

Hercules Overhead Reel

ALUMINIUM FRAME 6061-T6



**POWER DRAG
CARBON
WASHER**



Model	Handle Style	Color	Gear Ratio	Weight	Retrieve Per Crank	Max Drag	bearings	Line Capacity
CX1-L	Left	Silver/Gold Red/Gold	6.3:1	490g	98cm	25kg	13+2BB	PE2-450m PE3-300m/PE4- 250m
CX1-R	Right					25kg		
CX2-L	Left			520g	108cm	26kg		PE3-400m PE4- 300m/PE5- 250m
CX2-R	Right					26kg		

SOFIA Casting Reel

ALL METAL MANUFACTURING



Casting handle



Normal handle

Model	Color	Handle Style	Gear Ratio	Weight	Max Drag	Variable Brake System	bearings	Line Capacity
300	Gold	Right	6.2:1	310g	7kg	√	10+1BB	PE2-400m PE3-250m
301	Gold	Left						PE4-180m PE5-140m

G-MAX Spinning Reel

ALL METAL MANUFACTURING



Model	Bearings	Max Drag	Gear Ratio	Weight	Line Capacity
S-4000	10+1BB	20KG	4.7:1	295g	PE1.5-300m PE2-220m PE3-150m
S-5000	10+1BB			303g	PE1.5-350m PE2-260m PE3-180m

Custom EVA Reel Handle

Fit for refitting reel

Model:HG-1

Shimano/Daiwa/Abu/Megabass & ETC :

.Ocea jigger
.Trinidad A
.Ocea Jigger EV
.Torium
.Ocea Conquest
.Force Master

.Calcutta Conquest
.Tranx
.Tekota
.Beast Master
.Ocea Jigger (Limited)
.Calcutta

.Saltiga Z20/30
.Saltiga 15HC/15H
.Ryoga
.Catalina
.Millionaire
.Lexa-HD
.Leobritz

.Tatula - HD
.Coastal
.Saltist
.Sealine
.Seaborg
.Tanacom

.Ambassadeur Series
.Revo Inshore
.Revo Black 9
.Revo Salty Stage SJ
.Revo Bigshooter Compact

.Revo Power Crank
.Orange Max 3
.Orra Inshore
.Blue max
.Salty Stage Revo BJ

.Retgraph FIII
.Lin 10 Series
.Monoblock Series

5X8mm



7X7mm




8X8mm




G-MAX PE Line

- Made in japan
- No reel memory
- Smoother and slicker



WX8 braid
Near zero stretch



Color changes every 10m Mark every 1m

Size	Test	Length
3	20kg	200m/300m
4	26kg	200m/300m
5	32kg	200m/300m
6	37kg	300m
8	48kg	300m

Fluorocarbon leader line

Size: NO.#3-#50

Material From Japan
DESIGEND BY M&W



Size	Test(lb)	Diameter(mm)	Length(m)
#3	12	0.288	50
#4	16	0.341	
#5	19	0.381	
#6	26	0.410	
#8	32	0.480	
#10	40	0.515	
#12	46	0.565	
#14	52	0.615	
#16	56	0.650	
#18	64	0.690	
#20	70	0.735	
#22	76	0.770	
#24	84	0.810	
#30	100	0.890	
#40	132	1.060	
#50	150	1.160	

Fluorocarbon leader line

Fluorocarbon 50%

Nylon 50%

Size: NO.#8-#30

Material From Japan
DESIGEND BY M&W



Soft
Wear-Resisting
Low Extension

Size	Test(lb)	Diameter(mm)	Length(m)
#8	28	0.47	100
#10	35	0.52	100
#12	38	0.55	100
#14	42	0.60	100
#16	48	0.65	100
#18	56	0.70	50
#20	64	0.75	50
#25	78	0.85	50
#30	88	0.90	50

Nylon leader line

Material From Japan
DESIGEND BY M&W

Size: NO.#10-#50



Size	Test(lb)	Diameter(mm)	Length(m)
#10	35	0.52	100
#12	40	0.57	100
#14	50	0.62	100
#16	60	0.66	100
#18	70	0.70	100
#20	80	0.74	100
#24	90	0.81	50
#30	120	0.90	50
#40	150	1.05	50
#50	180	1.17	50

Assist Pe Line

Model: KW-1



X8 PE Line
 Double-decker setup
 Super wear-resistant

Hook \ Strength	3/0	5/0	7/0	9/0	11/0	13/0
200lb (4m)	←	→				
300lb (3.5m)		←	→			
400lb (3m)				←	→	



Assist Pe Line

Model: KW-2



X8 PE Line
 Double-decker setup
 Fluorocarbon line inside
 Super wear-resistant

Hook \ Strength	1/0	2/0	3/0	4/0	5/0	7/0
100lb (5m)	←	→				
200lb (4m)		←	→			
300lb (3.5m)				←	→	



Assist Kevlar Line

Model: KY-1



High-strength Kevlar material
 Hollow structure
 Super wear-resistant

HOOK \ Strength	3/0	5/0	7/0	9/0	11/0	13/0
200lb (4m)	←	→				
300lb (3.5m)		←	→			
400lb (3m)				←	→	



Assist Pe Line

Model: KG-1



7X7 stainless Steel Wire inside



glow-in-the-dark

Hook Strength	1/0	3/0	5/0	7/0	9/0	11/0
100lb (4m)	←	→				
200lb (4m)		←	→			
300lb (4m)				←	→	




Stainless Steel Wire



Material: 304 Stainless Steel
 7X7 Structure
 super wear-resistant
 As soft as fishing line

Diameter (mm)	Strength (kg/lb)	Length (m)
0.35	7/16	3
0.5	16/35	5
0.8	25/55	5
1.0	30/66	5



Assist Kevlar Line



Model	Strength (lb)	Length (cm)	Pcs
Q-1	300	16	5
	400		
Q-2	300	20	
	400		
Q-3	300	24	
	400		





M&W FISHING TACKLE Co.,Ltd.

Websit: <https://www.mwjigging.com>

Tel: +86580-2085611

Email: info@mwjigging.com